

# Actuator

45-2234.11H0.000





https://www.eao.com/component/45-2234.11H0.00...

## Your product:



## 45-2234.11H0.000 Actuator

		$\sim$		_
-	к		N	
		$\overline{}$	u.	

Front dimension: Ø 29,5 mm

Front form: Round

Front bezel colour: Black

Front bezel material: Plastic

#### **MOUNTING**

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

#### **OPERATING-/INDICATION PART**

Lens colour: Green

Lens material: Plastic

Lens illumination: Illuminated

Lens shape: Flush

**Lens optics:** transparent

**Lens type:** Level with front bezel


Illumination colour: Green

#### **MECHANICAL CHARACTERISTICS**


Switching action: Maintained

Switching system: Slow-make switching element

Mechanical lifetime:	500 000 cycles of operation	
Operating frequency:	Max. 1 800/h	
Weight:	0.02 kg	
AMBIENT CONDITION		
IP front protection:	IP66, IP67, IP69K	
Operating temperature:	– 25 °C + 70 °C	
Storage temperature:	– 40 °C + 80 °C	
Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms	
Vibration resistance:	According to IEC 60068-2-6: 20 500 Hz: 5 g	
Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6	
CERTIFICATE		
REACH:	REACH compliant	
RoHS:	RoHS compliant	
OTHER		
Short Description:	Actuator, Ø 22.3 mm, Ø 29,5 mm, Flush, Illuminated, Green, Plastic, transparent Round, Black, Plastic, Maintained, IP66, IP67, IP69K, Green	
Housing colour:	Black	
Housing material:	Plastic	
Product attributes:	Push to unlatch	
Hints:	Push to unlatch	
Wiring diagrams:		



## Mounting cut-outs:



### Dimension drawings:

