

Actuator

45-2729.1010.000







45-2729.1010.000 Actuator

_	_	_		-
-	к	u	N	

Front dimension: Ø 29 mm

Front form: Round

Front bezel colour: Black

Front bezel material: Plastic

MOUNTING

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens colour: Black

Lens material: Plastic

Lens illumination: Non illuminated

Lens shape: Raised

Lens optics: opaque

Lever colour: Black

Lever material: plastic


Lever shape: round

MECHANICAL CHARACTERISTICS

Switching action: Maintained

Release type:	Twist to unlock	
Mechanical lifetime:	300 000 cycles of operation	
Operating frequency:	Max. 600/h	
Weight:	0.018 kg	
AMBIENT CONDITION		
IP front protection:	IP66, IP67, IP69K	
Operating temperature:	– 25 °C + 70 °C	
Storage temperature:	– 40 °C + 80 °C	
Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms	
Vibration resistance:	According to IEC 60068-2-6: 20 500 Hz: 5 g	
Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6	
CERTIFICATE		
REACH:	REACH compliant	
RoHS:	RoHS compliant	
OTHER		
Short Description:	Actuator, Ø 22.3 mm, Ø 29 mm, Raised, Non illuminated, Black, Plastic, opaque, non illuminative, Black, round, Round, Black, Plastic, Maintained, IP66, IP67, IP69K, Twist to unlock	
Dimension:	Ø 29 mm	
Housing material:	Plastic	
Product attributes:	Twist to release, can be latched after pressing by rotating to the right	
Wiring diagrams:		
	(

Mounting cut-outs:



Dimension drawings:

