

# Actuator

46-  
2131.1180.000



<https://www.eao.com/component/46-2131.1180.00...>

Your product:

---



## 46-2131.1180.000 Actuator

### FRONT

|                              |         |
|------------------------------|---------|
| <b>Front dimension:</b>      | Ø 29 mm |
| <b>Front form:</b>           | Round   |
| <b>Front bezel colour:</b>   | Black   |
| <b>Front bezel material:</b> | Plastic |

### MOUNTING

|                          |                |
|--------------------------|----------------|
| <b>Design:</b>           | Raised         |
| <b>Mounting cut-out:</b> | Ø 22.3 mm      |
| <b>Mounting type:</b>    | Panel mounting |

### OPERATING-/INDICATION PART

|                           |                        |
|---------------------------|------------------------|
| <b>Lens colour:</b>       | Grey                   |
| <b>Lens material:</b>     | Plastic                |
| <b>Lens illumination:</b> | Non illuminated        |
| <b>Lens shape:</b>        | Flush                  |
| <b>Lens optics:</b>       | opaque                 |
| <b>Lens type:</b>         | Level with front bezel |

### ELECTRICAL CHARACTERISTICS

|                          |                                 |
|--------------------------|---------------------------------|
| <b>Pollution degree:</b> | 3                               |
| <b>Protection class:</b> | II, according to EN / IEC 61140 |

## MECHANICAL CHARACTERISTICS

|                             |                                  |
|-----------------------------|----------------------------------|
| <b>Switching action:</b>    | Momentary                        |
| <b>Mechanical lifetime:</b> | 1 Mil. cycles of operation       |
| <b>Tightening torque:</b>   | 2 ... 3 Nm (17.7 ... 26.6 Lb-in) |
| <b>Weight:</b>              | 0.022 kg                         |

## AMBIENT CONDITION

|                               |  |
|-------------------------------|--|
| <b>IP front protection:</b>   | IP65   |
| <b>IK front protection:</b>   | IK03   |
| <b>Operating temperature:</b> | - 25 °C ... + 55 °C  |
| <b>Shock resistance:</b>      | 30g, 18ms (EN-IEC 60068-2-27)<br>50g, 11ms (EN-IEC 60068-2-27) |
| <b>Vibration resistance:</b>  | 5g f= 2...500Hz (EN-IEC 60068-2-6)                             |
| <b>Climate resistance:</b>    | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)                   |

## CERTIFICATE

|                      |  |
|----------------------|--|
| <b>Approbations:</b> | CSA, EAC, UL                                       |
| <b>Conformities:</b> | CE   |
| <b>REACH:</b>        | REACH compliant                                    |
| <b>RoHS:</b>         | RoHS compliant                                     |
| <b>Standards:</b>    | CSA C22-2, IEC EN 60947-1, IEC EN 60947-5-1, UL508 |

## OTHER

|   |   |
|---|---|
| <b>Short Description:</b>                 | Actuator, Ø 22.3 mm, Ø 29 mm, Flush, Non illuminated, Grey, Plastic, opaque, Round, Black, Plastic, Momentary, IP65, IK03 |
| <b>Housing colour:</b>                    | Black   |
| <b>Housing material:</b>                  | Plastic   |
| <b>max. number of switching elements:</b> | 8   |
| <b>Mounting cut-outs:</b>                 |   |



**Dimension drawings:**

