

Actuator

704.741.8







704.741.8 Actuator

_	_	_		-
-	к	u	N	

Front dimension: 35 mm x 35 mm

Front form: Square

Front bezel colour: Silver

Front bezel material: Plastic

MOUNTING

Design: Flush

Mounting cut-out: 30 mm x 30 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens illumination: Illuminated

ELECTRICAL CHARACTERISTICS


Standards: The switches comply with the "Standards for low-voltage switching devices" DIN

EN 60947-1

MECHANICAL CHARACTERISTICS

Switching action:	Momentary	
Mechanical lifetime:	≤3 Mil. cycles of operation	
Operating force:	6.2 N	
Operating Travel:	ca. 5.8 mm ± 0.2 mm	
Weight:	0.018 kg	
AMBIENT CONDITION		
IP Protection:	IP65 front side	
Operating temperature:	– 40 °C + 55 °C	
Storage temperature:	– 40 °C + 85 °C	
CERTIFICATE		
REACH:	REACH compliant	
RoHS:	RoHS compliant	
OTHER		
Short Description:	Actuator, 30 mm x 30 mm, 35 mm x 35 mm, Illuminated, Square, Silver, Plastic, Momentary	
Housing colour:	Black	
Housing material:	Plastic	
Hints:	Max. 3 switching elements can be clipped on	
max. number of switching elements:	3	
Wiring diagrams:		


Mounting cut-outs:




A = Screw terminal

B = Push-in terminal (PIT)
C = Plug-in terminal 6.3 mm x 0.8 mm
D = Double plug-in terminal 6.3 mm x 0.8

Dimension drawings:



A = Screw terminal



A = Screw terminal